

The Description of HDT5350THB-42/45 Concrete Pump Truck:

1. Using imported engine, with powerful and stable performance
2. The transmission system imported from Germany
3. Drive mode stability
4. Imported steering gear with flexible and reliable features
5. Use PLC controller and other imported components.
6. Remote control using the HBC products
7. Boom welding of high strength materials, to be reliable construction.



The Technical Parameters of HDT5350THB-42/45 Concrete Pump Truck:

Specification	Unit	Value
output in theory	m ³ /h	125
index of the pump carry capacity	Mpa.m ³ /h	586
Theoretic pumping pressure	Mpa	8.5
bucket volume	L	700
height of top surface of bucket	mm	1400
model of distribution valve		S Valve
max. operation radius	m	38 40.7
max. operation height	m	41.8 44.7
max. operation depth	m	29 31.3
open height of boom	mm	8600 8495
distance between front landing legs	mm	8820 9550
distance between rear landing legs	mm	8500 9550
distance between front & rear landing legs	mm	8490 9190
diameter of delivery pipe	mm	125
length of hose pipe	m	3
rotary range of boom		365°
quantity of boom		4 5
rotary angle of each boom	°	92/180/180/240 91/180/180/180/270
wire line control distance	m	33

Contact us url : <https://www.concretebatchplant24.com> Email: onlinehcx@gmail.com

remote control distance	m	200
max. speed	km/h	85 80
min. turn radius	mm	12100
brake distance	m	10
approach angle	°	16
departure angle	°	11
chassis model		HOWO ZZ5437S4667C
wheel base between the first & the second axle	mm	
wheel base between the second & the third axle	mm	4600
wheel base between the third & the fourth axle	mm	1350
front tread	mm	2022
rear tread	mm	1830
max. engine output power	kw	275(2200r/min)
max. engine output torque	n.m	1500 /(1100~1600 r/min)
max. gradient ability	%	37 35
fuel consumption	L/100km	38 40
(××) out dimension(L×W×H)	mm	13650×2490×3960 13300×2500×4000
total weight	kg	35000 40000