

The Description of HBT60S1413-112R Trailer

Concrete Pump:

HaoMei HBT series concrete pumps are concrete pumping machines, including S-valve series of high-pressure concrete pumps, Z-gate-valve series of medium-pressure concrete pumps and D-butterfly-valve series of low-pressure concrete pumps. HBT series concrete pumps are mainly used to pump concrete. This concrete pumping is widely used for the construction works in civil construction, bridge construction, electric power and other energy source facilities and so on.

The Features of HBT60S1413-112R Trailer

Concrete Pump:

1. Power system of trailer concrete pump
2. Electric control system of trailer concrete pump
3. Hydraulic system of trailer concrete pump
4. Pumping system of trailer concrete pump
5. Lubrication system of trailer concrete pump



The Technical Parameters of HBT60S1413-112R Trailer Concrete Pump:

Specification	Unit	Value
"Theory Concrete Output (Low / High Pressure)"	m ³ /h	60
"Concrete Pressure (Low / high pressure)"	Mpa	13/7.4
Hydraulic system pressure	Mpa	32
Rotation speed	r/min	1480
High / low pressure switch		Yes
Distribution valve		S valve
Pumping cylinder diameter/ Stroke	mm	195/1500
Main oil pump discharge	ml/r	110
Diesel engine	kw	112
Voltage/ Frequency	V/Hz	380/50
Hydraulic tank volume	L	400
Height of adding material	mm	1355
Hopper volume	m ³	0.8
Total mass	kg	5800
Concrete slump	mm	120-230
Aclinic Delivery distance	m	1200
Theory vertical pumping height	m	250
Dimension: L*W*H	mm	6240*2110*2550