

## Description of JS500 Concrete Mixer:

JS 500 Concrete Mixer is double shaft compulsory concrete mixer. More advantages of this concrete equipment:

1. To be operated independently as single
2. To be combined with PLD series compounding machine to form simple concrete batching plant, it can provide associated main machine for batching plant, and is applicable to large, medium and small scale prefabricated components plants and road, bridge, irrigation works, dock and civil building project
3. Mix hard concrete, quaking concrete, fluidity concrete, light weight aggregate concrete.
4. This series of machine has a rational design structure, with new arrangement, and is easy to be repaired and used.
5. The height of leg like supports are designed as: JS500 is 1500mm, JS750 is 1600mm, JS1000 and JS1500A are 4600mm, among which (JS 1500B, JS2000 and JS3000 use Italian SICOMA technology).
6. The customer can use the mixer combined with tip lorry, dump truck, and mixer truck.

## Features of JS500 Concrete Mixer:

1. Excellent mixing performance
2. Wear-resisting lining board
3. Shaft-end sealing technology
4. Multiple protection devices
5. Heavy-duty design, easy to operate and low noise

## Technical Parameters of JS500 Concrete Mixer:





### Technical Parameters of JS500 Concrete Mixer:

Specification	Unit	Value
Discharging Volume	L	500
Charging Volume	L	800
Mixer Capacity	m3	0.5
Lubrication System	Brand	Chooosed
Reducer	Brand	Chooosed
Aggregate Size	mm	60/80
Aggregate Category	Quantity	4
Working Circle	S	60
Mixer Motor Power	KW	18.5
Mixing Speed	r/min	35
Mixing Blade	Quantity	2x7
Lifting Motor Power	KW	5.5
Pump Motor Power	KW	0.75
Weight	KG	1500
Dimensions	mm	3030x2300x2680