

## Description of JS750 Twin Shaft Concrete Mixer:

1. JS750 compulsory concrete mixer is an engineering compulsory mixer. JS750 concrete mixer discharge 0.75 each party, also known as 0.75 square concrete mixer, which often used as a host of HZS35 wet mix concrete batching plant.
2. JS750 concrete mixer theory productivity 35m<sup>3</sup> / h, duty cycle time is 60s, with a stirring force, small power consumption, strong power, built-in vortex mixer to prevent the material unity knot positions, etc., including the compulsory mixer planetary mixer, vortex mixer, agitator shaft, nesting agencies, discharge port , stand mixer and chassis components.
3. JS750 twin shaft compulsory concrete mixer is suitable for all types of large, medium and small prefabricated factories and roads, bridges, water conservancy, port and other industrial and civil engineering, which can mix dry concrete, plastic concrete, fluidity concrete, lightweight aggregate concrete and mortar variety, which is a high-efficiency model and widely used.





### The Technical Parameters of JS750 Concrete Mixer:

Specification	Unit	Value
Discharging Volume	L	750
Charging Volume	L	1200
Mixer Capacity	m3	0.75
Lubrication System	Brand	Chooosed
Reducer	Brand	Chooosed
Aggregate Size	mm	60/80
Aggregate Category	Quantity	4
Working Circle	S	60
Mixer Motor Power	KW	30
Mixing Speed	r/min	30.5
Mixing Blade	Quantity	2x8
Lifting Motor Power	KW	7.5
Pump Motor Power	KW	1.1
Weight	KG	6150
Dimensions	mm	4550x2250x2450